

# VIPER ELECTRIC DRUM ANCHOR WINCH RANGE COMPARISON

Motor power, voltage, drum diameter, fall rate and vessel suitability



| SPECIFICATIONS                               | ONYX<br>600W MICRO<br>(30080-N)                                      | TITAN<br>800W SERIES<br>(30082-N, 30083-N)                                                                                       | X-TREME<br>1000W SERIES<br>(30084-N, 30085-N)                                                                                    | X-TREME<br>GRAVITY FEED<br>(30086-N)                                   | VIPER<br>1500W SERIES<br>(30003-N)                                       | VIPER<br>2500W SERIES<br>(30004-N)                                       |
|----------------------------------------------|----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------|--------------------------------------------------------------------------|--------------------------------------------------------------------------|
| MOTOR POWER                                  | 600W                                                                 | 800W                                                                                                                             | 1000W                                                                                                                            | 1000W                                                                  | 1500W                                                                    | 2500W                                                                    |
| VOLTAGE                                      | 12V                                                                  | 12V                                                                                                                              | 12V                                                                                                                              | 12V                                                                    | 12V                                                                      | 24V                                                                      |
| DRUM DIAMETER                                | 200mm                                                                | MICRO 200mm<br>RAPID 250mm                                                                                                       | MICRO 200mm<br>RAPID 250mm                                                                                                       | 250mm                                                                  | 300mm                                                                    | 300mm                                                                    |
| MOTOR / IP RATING                            | Stainless Steel<br>IP68 Submersible                                  | Stainless Steel<br>IP68 Submersible                                                                                              | Stainless Steel<br>IP68 Submersible                                                                                              | Stainless Steel<br>IP68 Submersible                                    | IP68 Submersible<br>(S/S Comming Soon)                                   | IP68 Submersible<br>(S/S Comming Soon)                                   |
| MARINE GEAR BOX                              | Marine Grade<br>Anodized Marine<br>Aluminium                         | Marine Grade<br>Anodized Marine<br>Aluminium                                                                                     | 316 Stainless Steel                                                                                                              | 316 Stainless Steel                                                    | Marine Grade<br>Anodized Marine<br>Aluminium                             | Marine Grade<br>Anodized Marine<br>Aluminium                             |
| FALL RATE                                    | 45m/min                                                              | Micro: 45m/min<br>Rapid: 50/min                                                                                                  | Micro: 45m/min<br>Rapid: 50/min                                                                                                  | 138m/min                                                               | 55m/min                                                                  | 55m/min                                                                  |
| 316 S/S PLATE                                | 3mm                                                                  | 5mm                                                                                                                              | 8mm                                                                                                                              | 8mm                                                                    | 8mm                                                                      | 8mm                                                                      |
| ANCHOR DEPLOYMENT                            | Powered                                                              | Powered                                                                                                                          | Powered                                                                                                                          | Mechanical Free-Fall                                                   | Powered                                                                  | Powered                                                                  |
| EMERGENCY RELEASE                            | Included                                                             | Included                                                                                                                         | Included                                                                                                                         | Mechanical Free-Fall                                                   | Included                                                                 | Included                                                                 |
| RECOMMENDED<br>BOAT LENGTH                   | 4.5-6.5m                                                             | Micro: 4.5-7.8m<br>Rapid: 5.8-8.0                                                                                                | Micro: 4.5-7.5m<br>Rapid: 5.8-9.0                                                                                                | 5.8-9.0m                                                               | 9.0-12m                                                                  | 9.0-15m                                                                  |
| ROPE AND CHAIN<br>KIT OPTIONS                | (30045)<br>60m Rope & 6m Chain<br><br>(30056)<br>60m Rope & 6m Chain | MICRO - Same as ONYX<br><br>RAPID<br>30010 - 75m Rope & 8m Chain<br>30022 - 100m Rope & 8m Chain<br>30057 - 200m Rope & 8m Chain | MICRO - Same as ONYX<br><br>RAPID<br>30010 - 75m Rope & 8m Chain<br>30022 - 100m Rope & 8m Chain<br>30057 - 200m Rope & 8m Chain | (30022)<br>100m Rope & 8m Chain<br><br>(30059)<br>165m Rope & 8m Chain | (30026)<br>100m Rope & 10m Chain<br><br>(30027)<br>200m Rope & 10m Chain | (30026)<br>100m Rope & 10m Chain<br><br>(30027)<br>200m Rope & 10m Chain |
| WIRING LOOM<br>OPTION                        | 30080 - upto 6.5m<br>30081 - up 8.0m                                 | 30034 - upto 6.5m<br>30035 - up 9.0m                                                                                             | 30034 - upto 6.5m<br>30035 - up 9.0m                                                                                             | 30034 - upto 6.5m<br>30035 - up 9.0m                                   | Custom Looms<br>Available                                                | Custom Looms<br>Available                                                |
| WARRANTY                                     | 3 Years                                                              | 5 Years                                                                                                                          | 7 Years                                                                                                                          | 5 Years                                                                | 5 Years                                                                  | 5 Years                                                                  |
| RRP PRICING INC GST<br>(No Rope & Chain Kit) | \$1,379                                                              | MICRO: \$1,775<br>RAPID: \$1,880                                                                                                 | MICRO: \$2,085<br>RAPID: \$2,180                                                                                                 | \$2,825                                                                | \$2,695                                                                  | \$2,850                                                                  |

Complete winch bundle inc. all components except wiring loom. All RRP prices include GST.

ONYX is available as MICRO only. All Micro models have a fall rate of 45 m/min. All Rapid models have a fall rate of 50 m/min.